

Relays, Brackets, Conduit, Cable Ties, Cable

Relays



Part: RL-12V-40/30

12V 40/30 AMP 5-PIN Change Over Relay



Part: RL-24V-40/30

24V 10/20 AMP 5-PIN Change Over Relay



Part: RL-12V-15-F

12V 15AMP 5-PIN Relay, with 15-Amp built in fuse (includes fuse)



Part: RL-12V-30-F

12V 30AMP 5-PIN Relay, with 15-Amp built in fuse (includes fuse)

Conduit



NYLON FLEXIBLE CONDUIT

As used in the Fork-CAM Series Cables

This special black, flexible, nylon conduit has the advantages of being able to withstand temperatures from - 40°C to +120°C for static use and -30°C to +100°C for dynamic use; resists many oils, solvents and petrochemicals*; is extremely tough, has a high impact strength and a long fatigue life; UV resistant; halogen free; flame retardant and available in a wide range of sizes.

- Part: CON-NYL-8 100M Roll Bore 6.6mm, OD 10mm
- Part: CON-NYL-10 100M Roll Bore 8.4mm, OD 11.5mm
- Part: CON-NYL-12 100M Roll Bore 9.9mm, OD 13mm
- Part: CON-NYL-16 100m Roll Bore 12.7mm, OD 16.1mm

Brackets




Part: SOL-BRK

Bracket for Fork-SAFE Products:

- **SOL-M** (Speed-o-Limiter)
- **PC-C** (PAD-Start)

Suitable for various applications where mounting of items is required.




Max Weight: 5kg (non-moving vehicle). Allow lower weight capacity pending type of vehicle, product attached, and momentum of weight of environment.

Cable Ties

Cable Ties in Pack of 100



- Part: CT-25/100 2.5mm x 100mm
- Part: CT-25/155 2.5mm x 155mm
- Part: CT-25/196 2.5mm x 196mm
- Part: CT-35/202 3.5mm x 202mm
- Part: CT-35/295 3.5mm x 295mm
- Part: CT-48/370 4.8mm x 370mm
- Part: CT-90/530 9.0mm x 530mm



Self Adhesive Cable Tie Mounts

- Part: CT-ADH-25 Packet of 25
- Part: CT-ADH-50 Packet of 50
- Part: CT-ADH-100 Packet of 100

Cables



Part: CAB-4CS

4-Core, screened high quality 11/0.20 x 4 core +112/0.12
Color: red, white, yellow & Black.
Outer Dia: 6.2mm, 100m Roll.
(Available p/metre or roll)

Power Filter



Part: PF-001

In-Line Power Filter, 12v DC, 5A.